

Technical features:

- 8 mm. thick steel doors with laser cut between the frame and door
- Nickel-plated steel anti-sawing rolling dead-bolts (diameter 22 mm.)
- Seals are assembled through automated welding
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door


Standards:

- Manufactured in conformity with the UNI 10868:2000 Standards, grade 1 STAR resistance

Supplied as standard:

- Shelves
- Installation instructions
- Instruction sheet

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight	Pieces	ITEM				
			L	H	P							Type	Dim.	Hand	Fin.	Pers.



- Key only version
- 2 keys item 1.00100.00.2

	310	190	145	8	2	1	9,400	1	1	8A010 20 0					
	310	190	195	8	2	1	10,300	1	1	8A010 21 0					
*	360	240	145	8	2	1	12,650	1	1	8A010 30 0					
	360	240	195	8	2	1	13,650	1	1	8A010 31 0					
	420	300	195	8	2	1	18,100	1	1	8A010 40 0					
*	420	300	245	8	2	1	20,000	1	1	8A010 41 0					
*	490	360	195	8	2	2	24,550	1	1	8A010 50 0					
*	490	360	245	8	2	2	26,150	1	1	8A010 51 0					