



Technical features:

- 10 mm. thick steel front
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm.)
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe
- Opening commands do not protrude when in the rest position


On request:

- Safes with master code function (caratt. TF)

Supplied as standard:

- Power cable
- Shelves
- Use and maintenance instructions
- Installation instructions

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight Kg	Pieces	ITEM			
			L	H	P							Type	Dim.	Hand	Fin.



- Electronic combinator
- Internal light
- 1.5 V alkaline thin battery operation
- Removable door
- Laser welded sealing parts assembly

*	360	240	150	10	2	1	14,400	1	1 82610 30 0
*	360	240	200	10	2	1	15,400	1	1 82610 31 0
	360	240	250	10	2	1	16,700	1	1 82610 32 0
*	420	300	200	10	2	3	21,600	1	1 82610 40 0
*	420	300	250	10	2	3	23,100	1	1 82610 41 0
	420	300	300	10	2	3	24,900	1	1 82610 42 0
*	490	360	200	10	2	3	28,950	1	1 82610 50 0
*	490	360	250	10	2	3	30,000	1	1 82610 51 0
	490	360	300	10	2	3	31,750	1	1 82610 52 0
	360	490	200	10	2	3	29,350	1	1 82610 70 0
	360	490	250	10	2	3	31,000	1	1 82610 71 0
	360	490	300	10	2	3	32,700	1	1 82610 72 0

TO BE DISCONTINUED