




Technical features:

- Lit keypad.
- 10 mm thick steel front
- Seals are assembled using tough welds
- Nickel-plated steel dead-bolts (diameter 22 mm)
- Special high-resistance anti-corrosion kiln painting
- Carbonitrided steel lock protection plate
- Lock and mechanisms are fixed directly onto the door of the safe
- Opening commands do not protrude when in the rest position

Supplied as standard:

- Power cable
- Shelves
- Use and maintenance instructions
- Installation instructions.

Type	Description	Prompt delivery	Outside dim.			Door thickness	Vertical bolts	Horizontal bolts	No. of shelves	Unit weight	Pieces	ITEM			
			L	H	P							Type	Dim. Hand	Fin.	Pers. Spec.



- Electronic combinator
- Internal light
- 1.5 V alkaline thin battery operation
- Removable door
- Laser welded sealing parts assembly

			360	240	150	10	2	1	14,400	1	1 82710 30 0				
			360	240	200	10	2	1	15,400	1	1 82710 31 0				
			360	240	250	10	2	1	16,700	1	1 82710 32 0				
			420	300	200	10	2	3	21,600	1	1 82710 40 0				
			420	300	250	10	2	3	23,100	1	1 82710 41 0				
			420	300	300	10	2	3	24,900	1	1 82710 42 0				
			490	360	200	10	2	3	28,950	1	1 82710 50 0				
			490	360	250	10	2	3	30,000	1	1 82710 51 0				
			490	360	300	10	2	3	31,750	1	1 82710 52 0				
			360	490	200	10	2	3	29,350	1	1 82710 70 0				
			360	490	250	10	2	3	31,000	1	1 82710 71 0				
			360	490	300	10	2	3	32,700	1	1 82710 72 0				