



**MULTITOP**

**Technical features:**

- Geared operating device for reducing key effort
- Patented system to avoid out of phase operations
- Zinc plated steel case
- Stainless steel faceplate
- Nickel-plated latch, roller and horizontal-slide dead-bolt
- Latch or reversible latch/bolt (where this is provided for)
- Can be fitted with additional locking points
- Through-screws for fixing the handle rose

- Threaded pins for fixing the extended bolts
  - Lock and cylinder fixing screws
  - Instruction sheet
- On request:**
- Specific striking plates
  - Cylinder protective rose item 1.06460.05.0 or item 1.06460.06.0

**Hand:**  
0 = Non-handed


Cylinder to be ordered separately series 08710 or 0E300 (ASIX)



**Supplied as standard:**


- Set of nylon roses item 1.06012.01.0
- Set of nylon faceplate spacers item 1.06141.65.0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin. Pars. Spec.




- Dead-bolt and latch
- 10.5 to 16.5 mm. adjustable latch and piston
- 12 V ac CE
- ON REQUEST:
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0

2	85	22	25	0,920	1	1	18225 25 0
2	85	22	30	0,970	1	1	18225 30 0
2	85	22	35	0,990	1	1	18225 35 0



- Dead-bolt only
- ON REQUEST:
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0


2	-	22	25	0,640	12	1	48220 25 0
2	-	22	30	0,720	12	1	48220 30 0
2	-	22	35	0,740	12	1	48220 35 0



- Dead-bolt and latch
- 11 to 17 mm. adjustable latch
- ON REQUEST:
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0

2	85	22	25	0,700	12	1	48225 25 0
2	85	22	30	0,750	12	1	48225 30 0
2	85	22	35	0,820	12	1	48225 35 0

Type	Description	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM			
							Type	Dim. Hand	Fin.	Pers. Spec.



- Dead-bolt and roller
- 2.5 to 16.5 mm. adjustable roller
- ON REQUEST:
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0

2	-	22	25	0,700	12	1	48250	25	0
2	-	22	30	0,750	12	1	48250	30	0
2	-	22	35	0,800	12	1	48250	35	0