

Technical features:

- Zinc plated steel case.
- Stainless steel faceplate
- Can be fitted with additional locking points
- Spindle for operating the dead-bolt and reloading pins, which can be locked by key

Supplied as standard:


- Set of nylon roses item 1.06012.01.0
- Set of faceplate spacers item 1.06141.65.0
- Threaded pins for fixing the extended bolts
- Lock and cylinder fixing screws
- Instruction sheet

On request:


- Specific striking plates
- Cylinder protective rose item 1.06460.00.0

Hand:
0 = Non-handed

Cylinder to be ordered separately
series 08710 or 0E300 (ASIX)




Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin.




- Nickel-plated dead-bolt
- ON REQUEST:
 - Cross-key cylinder item 1.02400.10.0
 - Internal ragged extended bolts item 1.06441.00.0
 - Internal straight extended bolts item 1.06441.10.0
 - External bolt connectors item 1.06442.00.0
 - Extended bolts operated by internal rods item 1.06443.00.0
 - Extended bolts operated by external rods item 1.06443.05.0

1	85	22	25	0,620	12	1 46200 25 0
1	85	22	30	0,640	12	1 46200 30 0
1	85	22	35	0,610	12	1 46200 35 0



- Nickel-plated hook
- Stainless steel striking plate item 1.06459.01.0
- ON REQUEST:
 - Cross-key cylinder item 1.02400.10.0
 - Internal ragged extended bolts item 1.06441.00.0
 - Internal straight extended bolts item 1.06441.10.0
 - External bolt connectors item 1.06442.00.0
 - Extended bolts operated by internal rods item 1.06443.00.0
 - Extended bolts operated by external rods item 1.06443.05.0

1	85	22	25	0,650	12	1 46265 25 0
1	85	22	30	0,670	12	1 46265 30 0
1	85	22	35	0,693	12	1 46265 35 0



- No frontal closure
- ON REQUEST:
 - Cross-key cylinder item 1.02400.10.0
 - Internal ragged extended bolts item 1.06441.00.0
 - Internal straight extended bolts item 1.06441.10.0
 - External bolt connectors item 1.06442.00.0
 - Extended bolts operated by internal rods item 1.06443.00.0
 - Extended bolts operated by external rods item 1.06443.05.0

-	85	22	25	0,570	12	1 46275 25 0
-	85	22	30	0,540	12	1 46275 30 0
-	85	22	35	0,560	12	1 46275 35 0