



**Technical features:**

- Geared operating device for reducing key effort
- Patented system to avoid out of phase operations
- Lock modularity with additional locking points, 06444 series
- Zinc plated steel case
- Stainless steel faceplate
- Nickel-plated horizontal-slide dead-bolts with hardened steel inserts
- Nickel-plated latch and roller
- Latch or reversible latch/bolt (where this is provided for)
- Through-screws for fixing the handle rose

**Supplied as standard:**

- Set of nylon roses item 1.06012.0.10
- Nylon faceplate cover plugs
- Threaded pins for fixing the extended bolts
- Lock and cylinder fixing screws
- Instruction sheet

**On request:**

- Specific striking plates
- Cylinder protective rose item 1.06460.05.0 or 1.06460.06.0


**Hand:**  
0 = Non-handed

**Cylinder to be ordered separately series 08710 or 0E300 (ASIX)**



**MULTITCP**

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin.




- U-shaped faceplate 24 x 5 mm.
- Latch and dead-bolt
- 10.5 to 16.5 mm. adjustable latch and piston
- 12 V ac CE
- ON REQUEST:
  - Lateral bolts item 1.06444.15/16/17
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.00.0
  - Extended bolts operated by external rods item 1.06443.05.0

2	92	24	25	0,950	1	1	18128	25	0		
2	92	24	30	0,970	1	1	18128	30	0		
2	92	24	35	0,990	1	1	18128	35	0		

- U-shaped faceplate 24 x 7 mm.
- Latch and dead-bolt
- 10.5 to 16.5 mm. adjustable latch and piston
- 12 V ac CE
- ON REQUEST:
  - Lateral bolts item 1.06444.10/11/12
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0

2	92	24	25	0,950	1	1	18129	25	0		
2	92	24	30	0,970	1	1	18129	30	0		
2	92	24	35	0,990	1	1	18129	35	0		





- U-shaped faceplate 24 x 5 mm.
- Dead-bolt only
- ON REQUEST:
  - Lateral bolts item 1.06444.15/16/17
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0






2	-	24	25	0,700	1	1	48123	25	0		
2	-	24	30	0,720	1	1	48123	30	0		
2	-	24	35	0,740	1	1	48123	35	0		

- U-shaped faceplate 24 x 7 mm.
- Dead-bolt only
- ON REQUEST:
  - Lateral bolts item 1.06444.10/11/12
  - Internal ragged extended bolts item 1.06441.00.0
  - Internal straight extended bolts item 1.06441.10.0
  - External bolt connectors item 1.06442.00.0
  - Extended bolts operated by internal rods item 1.06443.20.0
  - Extended bolts operated by external rods item 1.06443.25.0

2	-	24	25	0,700	1	1	48124	25	0		
2	-	24	30	0,720	1	1	48124	30	0		
2	-	24	35	0,740	1	1	48124	35	0		

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> <li>• U-shaped faceplate 24 x 5 mm.</li> <li>• Latch and dead-bolt</li> <li>• 11 to 17 mm. adjustable latch</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Lateral bolts item 1.06444.15/16/17</li> <li>- Internal ragged extended bolts item 1.06441.00.0</li> <li>- Internal straight extended bolts item 1.06441.10.0</li> <li>- External bolt connectors item 1.06442.00.0</li> <li>- Extended bolts operated by internal rods item 1.06443.20.0</li> <li>- Extended bolts operated by external rods item 1.06443.25.0</li> </ul> </li> </ul>	2	92	24	25	0,780	1	1	48128	25	0	
		2	92	24	30	0,800	1	1	48128	30	0	
		2	92	24	35	0,820	1	1	48128	35	0	
		2	92	24	25	0,780	1	1	48129	25	0	
		2	92	24	30	0,800	1	1	48129	30	0	
		2	92	24	35	0,820	1	1	48129	35	0	
		2	92	24	25	0,780	1	1	48153	25	0	
		2	92	24	30	0,800	1	1	48153	30	0	
		2	92	24	35	0,820	1	1	48153	35	0	
		2	92	24	25	0,780	1	1	48154	25	0	
	<ul style="list-style-type: none"> <li>• U-shaped faceplate 24 x 5 mm.</li> <li>• Roller latch and dead-bolt</li> <li>• 2.5 to 16 mm. adjustable roller latch</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Lateral bolts item 1.06444.15/16/17</li> <li>- Internal ragged extended bolts item 1.06441.00.0</li> <li>- Internal straight extended bolts item 1.06441.10.0</li> <li>- External bolt connectors item 1.06442.00.0</li> <li>- Extended bolts operated by internal rods item 1.06443.20.0</li> <li>- Extended bolts operated by external rods item 1.06443.25.0</li> </ul> </li> </ul>	2	-	24	25	0,760	1	1	48153	25	0	
		2	-	24	30	0,780	1	1	48153	30	0	
		2	-	24	35	0,800	1	1	48153	35	0	
		2	-	24	25	0,760	1	1	48154	25	0	
		2	-	24	30	0,780	1	1	48154	30	0	
		2	-	24	35	0,800	1	1	48154	35	0	
		2	-	24	25	0,760	1	1	06444	10	0	
		2	-	24	30	0,780	1	1	06444	15	0	
		2	-	24	35	0,800	1	1	06444	20	0	
		2	-	24	25	0,760	1	1	06444	30	0	
	<ul style="list-style-type: none"> <li>• Set of modular lateral bolts with 24 x 7 mm. U-shaped faceplate</li> <li>• Pre-arranged for 4th and 5th locking points</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Threaded rod item 1.06449.05.0 for extended bolts (4th and 5th locking point)</li> </ul> </li> </ul>	2	-	24	-	2,050	1	1	06444	10	0	
	<ul style="list-style-type: none"> <li>• Set of modular lateral bolts with 24 x 5 mm. U-shaped faceplate</li> <li>• Pre-arranged for 4th and 5th locking points</li> <li>• ON REQUEST:                             <ul style="list-style-type: none"> <li>- Threaded rod item 1.06449.05.0 for extended bolts (4th and 5th locking point)</li> </ul> </li> </ul>	2	-	24	-	1,950	1	1	06444	15	0	

Type	Description	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM							
							Type	Dim.	Hand	Fin.	Pers. Spec.			
	<ul style="list-style-type: none"> <li>• Modular top lateral bolt with 24 x 7 mm. U-shaped faceplate</li> <li>• Pre-arranged for 4th locking point</li> <li>• ON REQUEST: - threaded rod item 1.06449.05.0 for extended bolt</li> </ul>	2	-	24	-	0,825	1	1	06444	11	0			
	<ul style="list-style-type: none"> <li>• Modular top lateral bolt with 24 x 5 mm. U-shaped faceplate</li> <li>• Pre-arranged for 4th locking point</li> <li>• ON REQUEST: - threaded rod item 1.06449.05.0 for extended bolt</li> </ul>	2	-	24	-	1,002	2	1	06444	16	0			
	<ul style="list-style-type: none"> <li>• Modular bottom lateral bolt with 24 x 7 mm. U-shaped faceplate</li> <li>• Pre-arranged for 5th locking point</li> <li>• ON REQUEST: threaded rod item 1.06449.05.0 for extended bolt</li> </ul>	2	-	24	-	0,675	1	1	06444	12	0			
	<ul style="list-style-type: none"> <li>• Modular bottom lateral bolt with 24 x 5 mm. U-shaped faceplate</li> <li>• Pre-arranged for 5th locking point</li> <li>• ON REQUEST: - threaded rod item 1.06449.05.0 for extended bolt</li> </ul>	2	-	24	-	0,900	2	1	06444	17	0			

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Peris. Spec.
	<ul style="list-style-type: none"> <li>• Flat faceplate 24 x 3 mm.</li> <li>• Latch and dead-bolt</li> <li>• 2.5 to 16.5 mm. adjustable latch and piston</li> <li>• 12 V ac CE</li> <li>• ON REQUEST: Lateral bolts item 1.06444.20/21/22 Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.00.0 Extended bolts operated by external rods item 1.06443.05.0</li> </ul>	2	92	24	25	0,950	1	1	18229	25	0	
		2	92	24	30	0,970	1	1	18229	30	0	
		2	92	24	35	0,990	1	1	18229	35	0	
	<ul style="list-style-type: none"> <li>• Flat faceplate 24 x 3 mm.</li> <li>• Dead-bolt only</li> <li>• ON REQUEST: Lateral bolts item 1.06444.20/21/22 Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.20.0 Extended bolts operated by external rods item 1.06443.25.0</li> </ul>	2	-	24	25	0,700	1	1	48224	25	0	
		2	-	24	30	0,720	1	1	48224	30	0	
		2	-	24	35	0,740	1	1	48224	35	0	
	<ul style="list-style-type: none"> <li>• Flat faceplate 24 x 3 mm.</li> <li>• Latch and dead-bolt</li> <li>• 11 to 17 mm. adjustable latch</li> <li>• ON REQUEST: Lateral bolts item 1.06444.20/21/22 Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.20.0 Extended bolts operated by external rods item 1.06443.25.0</li> </ul>	2	92	24	25	0,780	1	1	48229	25	0	
		2	92	24	30	0,800	1	1	48229	30	0	
		2	92	24	35	0,820	1	1	48229	35	0	
	<ul style="list-style-type: none"> <li>• Flat faceplate 24 x 3 mm.</li> <li>• Roller latch and dead-bolt</li> <li>• 2.5 to 16.5 mm. adjustable roller latch</li> <li>• ON REQUEST: Lateral bolts item 1.06444.20/21/22 Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.20.0 Extended bolts operated by external rods item 1.06443.25.0</li> </ul>	2	-	24	25	0,760	1	1	48254	25	0	
		2	-	24	30	0,780	1	1	48254	30	0	
		2	-	24	35	0,800	1	1	48254	35	0	
	<ul style="list-style-type: none"> <li>• Set of modular lateral bolts with 24 x 3 mm. flat faceplate</li> <li>• Pre-arranged for 4th and 5th locking points</li> <li>• ON REQUEST: Threaded rod item 1.06449.05.0 for extended bolts (4th and 5th locking point)</li> </ul>	2	-	24		2,100	1	1	06444	20	0	

Type	Description	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM				
							Type	Dim.	Hand	Fin.	Pers. Spec.



- Modular top lateral bolt with 24 x 3 mm. flat faceplate
- Pre-arranged for 4th locking point
- ON REQUEST:  
Threaded rod item 1.06449.05.0 for extended bolt

2 - 24 0,825 2 1 06444 21 0



- Modular bottom lateral bolt with 24 x 3 mm. flat faceplate
- Pre-arranged for 5th locking point
- ON REQUEST:  
Threaded rod item 1.06449.05.0 for extended bolt

2 - 24 - 0,675 2 1 06444 22 0