



Technical features:

- Painted protective steel case
- Metal striker with stainless steel swinging pin
- Rotary hook deadbolt in extruded aluminium
- 12 ac CE
- Non-handed and with a variable backset from 50 to 80 mm

Supplied as standard:

- Striker
- Instruction sheet
- Fixing screws
- 2 spacers for the striker
- 3 keys item 1.01070.10.1


On request:

- Booster item 1.07022.00.0
- Booster plus item 1.07022.10.0
- BTicino coil item 1.07025.10.0
- Microswitch device 1.07023.00.0

Hand:

0 = Non-handed

| Type | Description | Cylinder | Throws | Backset | Unit weight Kg | Pieces | ITEM | | | | |
|------|-------------|----------|--------|---------|-------------------|--------|------|------|------|------|-------------|
| | | | | | | | Type | Dim. | Hand | Fin. | Pers. Spec. |



- Inner push-button




Art.
1 0G500 00 0

- 50 2,450 1 1 1A610 00 0



Art.
1 0G200 55 0

- 50 2,350 1 1 1A611 00 0



- Inner push-button
- Hold open device



Art.
1 0G115 00 0

- 50 2,500 1 1 1A630 00 0



Art.
1 0G150 00 0

- 50 2,350 1 1 1A631 00 0