



Technical features:

- Steel case
- Steel faceplate
- Lamellar steel deadbolt protected by single throw armour plating
- 13 mm driving gears stroke for additional locking points
- Spindle for operating the dead bolt and driving gears
- Dead bolt resistance according to Class 3, CEN standard, prEN 12209: 2002 Security sections 5.8.2.1 and 5.8.6.
- Resistance to lateral load (up to 1000 kg) in conformity with the highest levels indicated by the relevant standards.

Finishes:

- Zinc-plated case
- Zinc-plated faceplate
- Zinc-plated deadbolt

Hand:


0 = Non-handed

Cylinder to be ordered separately




0G303, 0G305, 0E303, 0E305

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin.



- Latch bolt only
- CAN BE USED WITH THE FOLLOWING ACCESSORIES:
- European profile cylinders with special cam:
 - Item 1-0G305-02-0-12 (C2000 single cylinder)
 - Item 1-0G303-07-0-12 (C2000 double cylinder)
 - Item 1-0E305-02-0-12 (ASIX single cylinder)
 - Item 1-0E303-07-0-12 (ASIX double cylinder)
- Handle art. 1-06003-00-0
- Handle with edge cover art. 1-06004-00-0
- Striking plate art. 1-06232-21-0
- Adjustable striking plate art. 1-06232-22-0
- Screwed extended bolts art. 1-07088-03-0

1	59	25	19,7	0,590	24	1	46305	19	0		
1	59	25	25,7	0,685	24	1	46305	25	0		
1	59	25	31,7	0,780	24	1	46305	30	0		



- Dead bolt only
- Pin key cylinder complete with 2 pieces item 1.00210.00.0 (KA 1 version, key included)
- CAN BE USED WITH THE FOLLOWING ACCESSORIES:
 - Handle item 1.06003.01.0
 - Handle with edge cover item 1.06004.01.0
 - Striker item 1.06232.21.0
 - Adjustable striker item 1.06232.22-0
 - Extended bolts item 1.07088.03.0

1	59	25	19,7	0,709	24	1	46307	19	0		
1	59	25	25,7	0,804	24	1	46307	25	0		
1	59	25	31,7	0,923	24	1	46307	30	0		